



MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO			SCDFLR			
MATERIAL			HOUSING-PC+GF			
			LENS-PC			
			PROTECTION CAGE-SUS316L			
			REFLECTOR-PC			
COLOR OF LENS			RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.			120 ~ 140			
USE VOLT.	LED	CURRENT	DC12V	1W	MAX. 2.633A	
			DC24V		MAX. 1.288A	
			AC110V		MAX. 0.308A	
			AC220V		MAX. 0.154A	
KIND OF SOUND			WS	5 Warning Sounds		
			WP	5 Special Warning Sounds		
			WM	5 Melodies		
			WA	5 Alarms		
			WV	5 Customizable Sounds		
VOLUME			MAX. 118dB at 1m			
PROTECTION GRADE			WATER & DUST PROOF IP66			
CABLE ENTRY			1/2"PF			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH		-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	(C)	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-			DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW
	3~6			±0.3	±0.5			S.H.KIM	J.H.PARK		J.K.HAN	DATE
	6~30	±0.1	±0.2	±0.5	±1							3
	30~120	±0.15	±0.3	±0.8	±1.5							2019.03.26
	120~400	±0.2	±0.5	±1.2	±2.5			TITLE		SCDFLR		
FOR ANGULAR DIMENSIONS	0~10	±1°	±1°30'	±3°				MODEL		SCDFLR		
	10~50	±0°30'	±1°	±2°				DWG. NO.		SCDFLR_OUT		
	50~120	±0°20'	±0°30'	±1°				SCALE		SIZE	REV	SHEET
	120~400	±0°10'	±0°13'	±0°30'				N/S		A4	00	1/1

