




POWER CABLE
22AWG(10CORE)

360°/3-
M4 BOLT



ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS	0.5~3	f ±0.05	m ±0.1	⌀ ±0.2	v -
	3~6			±0.3	±0.5
	6~30	±0.1	±0.2	±0.5	±1
	30~120	±0.15	±0.3	±0.8	±1.5
	120~400	±0.2	±0.5	±1.2	±2.5
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4
	0~10	±1°		±1°30'	
	10~50	±0°30'		±1°	
	50~120	±0°20'		±0°30'	
	120~400	±0°10'		±0°13'	

SURFACE
FINISH

-	-	-	-	1	-	
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QT'Y	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
J.H.PARK	J.K.HAN		J.I.BAE	3	2023.02.03	
TITLE			MODEL			
ST45ML-NEC OUTLINE DRAWING			ST45ML-NEC			
			DWG. NO.			
			ST45ML-NEC_OUT			
SCALE		SIZE	REV	SHEET		
N/S		A4	00	1/1		

MARK	DATE	REVISION	REVISER	APP .BY
1				
2				
3				

MODEL NO		ST45ML-NEC	
MATERIAL		HOUSING-PC	
		LENS-PC	
		COVER-AL	
		UNDER BODY-AL	
COLOR OF LENS		RED,AMBER,GREEN	
USE VOLT.	CURRENT	DC24V	0.036A
PROTECTION GRADE		WATER & DUST PROOF IP54	
CABLE ENTRY		M16	
COLOR OF HOUSING		MAKER STANDARD	
ACTION		LED STEADY LIGHT	